

seaco

FLATRACKS

SPECIFICALLY DESIGNED FOR HEAVY CARGO SUCH AS PIPE WORK AND MACHINERY

FLATRACKS HAVE COLLAPSIBLE END WALLS, IDEAL FOR STACKING, STORAGE AND TRANSPORTATION BY RAIL, ROAD OR SEA



GLOBAL EXPERTISE WITH LOCAL KNOWLEDGE

FEATURES

- HEAVY DUTY FLOORS
 - 35 MM FOR 20FT
 - 45 MM FOR 40FT
- CORTEN STEEL CROSSMEMBERS AND END WALLS
- MULTIPLE LOADING OPTIONS
- COLLAPSIBLE END WALLS
- LASHING BARS
- EXCELLENCE IN QUALITY ASSURANCE AND DEPOT REPAIR PROCEDURES
- EPOXY ZINC RICH PRIMER APPLIED TO SURFACES (EXCLUDING WOODEN FLOOR)

ADVANTAGES

- HIGH DURABILITY
- PROVIDES EXTRA STRENGTH
- SUITABLE FOR ABNORMAL LOADS
- EASILY STACKED TOGETHER FOR STORAGE AND BACKHAUL
- SECURING CARGO
- EXTENDS IN-SERVICE LIFE
- REDUCES CORROSION
- IMPROVES COSMETIC APPEARANCE

BENEFITS

- REDUCES M&R COSTS
- REDUCES M&R COSTS
- ALLOWS CARGO THAT CANNOT FIT INSIDE A STANDARD CONTAINER TO BE TRANSPORTED IN AN INTERMODAL ENVIRONMENT IN A COST EFFECTIVE WAY
- SAVING COSTS
- ALLOWS CARGO THAT CANNOT FIT INSIDE A STANDARD CONTAINER TO BE TRANSPORTED IN AN INTERMODAL ENVIRONMENT
- REDUCES M&R COSTS
- PROTECTS CORTEN STEEL
- REDUCES M&R COSTS

ANTWERP • BRISBANE • CAPE TOWN • GOTHENBURG • HAMBURG • HOUSTON • LISBON • LONDON • MADRID • MIAMI
 MOSCOW • MUMBAI • PARIS • PERTH • RIO DE JANEIRO • SEOUL • SHANGHAI • SINGAPORE • SYDNEY • TAIPEI • TOKYO

**DRY FREIGHT SPECIALS: BULKERS, FLATRACKS, OPEN TOPS,
 HALF HEIGHTS, ROLLTRAILERS, SEACELLS, SEAPC⁺,
 SLIMWALL CPC[®]S AND 2.5m PALLETWIDES**



TECHNICAL SPECIFICATIONS	20ft	40ft
Maximum Gross Weight	34,000 kgs	52,500 kgs
Tare Weight	2,800 kgs	5,100 kgs
Payload	31,200 kgs	47,400 kgs
Concentrated Load	20,000 kgs (over centre 2 m span)	30,000 kgs (over centre 2 m span)
Stacking	7 high at 34,000 kgs	8 high at 30,480 kgs or 5 high at 52,500 kgs
Internal Length (Between End Panels)	6,038 mm	12,064 mm
Internal Length (Between Corner Posts)	5,632 mm	11,652 mm
Internal Width (Over Bottom Side Rail)	2,194 mm	2,374 mm
Internal Width (Between Corner Posts)	2,226 mm	2,212 mm
Bundling for Intermodal Use	7 per bundle (some ports might vary)	4 per bundle
Lashing Points (Maximum Allowable Load)	5,000 kgs each	5,000 kgs each

SEACO HAS A DEDICATED TEAM OF WORLDWIDE SPECIALISTS WHO HAVE CONSTRUCTED ONE OF THE LARGEST LEASING FLEETS OF SPECIALISED CONTAINERS. WITH OUR VAST EXPERIENCE IN THE INDUSTRY, WE WILL FIND THE RIGHT PRODUCT FOR YOUR NEEDS AND TAILOR OUR LEASE AGREEMENTS TO YOUR SPECIFIC REQUIREMENTS.

FOR DETAILED SPECIFICATIONS OF OUR PRODUCT OFFERING, PLEASE CONTACT YOUR REGIONAL SEACO OFFICE:

AMERICAS

(+1) 281 377 3200 ext. 2131
 cs.americas@seacoglobal.com

EUROPE

(+49) 40 8080 3128
 cs.emeia@seacoglobal.com

MIDDLE EAST & INDIA

(+91) 22 6179 0644
 cs.isc@seacoglobal.com

AFRICA

(+27) 2 1702 3631
 cs.southafrica@seacoglobal.com
 seacoglobal.co.za

ASIA

(+65) 6595 1900
 cs.asiapacific@seacoglobal.com

OCEANIA

(+61) 2 9290 1455
 cs.oceania@seacoglobal.com
 seacoglobal.com.au



an **HNA** company